



DESCRIPTION		Diamalite		Pureclean
Total thickness	EN ISO24346	mm	2.00	2.00
Wearlayer thickness	EN ISO24340	mm	0.20	0.25
Poids	EN ISO 23997	g/m ²	1370	1390
Weight	EN ISO 24341	cm	200 / 300 / 400	
Width of sheet	EN ISO 24341	ml	≈ 25	
CLASSIFICATION				
Norm / Product specification	-	-	EN ISO 26986	
European classification	EN ISO 10874	class	22	23 - 31
Impact sound insulation	EN ISO 717-2	dB	15	
Walk noise	NFS 31 074	dB	≤ 65	
Fire rating	EN 13 501-1	class	Cfls1	
Static electrical propensity	EN 1815	kV	< 2	
Slip resistance wet : ramp test with oil	DIN 51130	class	R10	
PERFORMANCE				
Wear group	-	group	T	
Dimensional stability (requirement)	EN ISO 23999	%	≤ 0.40	
Dimensional stability (average measured value)	-	%	0.05	
Residual indentation (requirement)	EN ISO 24343-2	mm	≤ 0.35	
Residual indentation (average value measured)		mm	0.25	0.20
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	
Colour fastness	EN 20 105 - B02	degree	≥ 6	
Surface treatment	-	-	Diamalite	Pureclean
Chemical products resistance	EN ISO 26987	class	ok	
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 100	
Certification	-	-	Floorscore®	
CE MARKING				
	EN 14041	-		
		-	